

Insulated tubular cable lugs, Cu, standard type



- ▶ For multi-stranded conductors e.g. VDE 0295 Class 2
- ▶ For pre-rounded multi-stranded sector shaped conductors
- ▶ No additional insulation of the crimped connection required

Characteristics

- Total cross-section: 10 - 150 mm<sup>2</sup>
- Is directly crimped with the insulation
- Annealed material optimises material and crimping properties
- Precise end machining for easy cable insertion
- Heat resistant to 105° C

Material


- Cable lug: Copper acc. to EN 13600
- Insulation sleeve: PA, halogen-free

Surface

- Tin-plated

Order info

- Also available with inspection hole, part number appendix "ms"



Nominal cross section mm <sup>2</sup>	Size of bolt dia.	Part No.	Colour	Dimension mm						Weight 100 pcs. ~kg		Packing unit/ pcs
				d12	d13	d2	G11	l10	Cu	Total		
10	M5	602R5	Red	7.0	9.0	5.5	35.5	17.0	0.50	0.548	25	
	M6	602R6	Red	7.0	9.0	6.5	35.5	17.0	0.49	0.538	25	
	M8	602R8	Red	7.0	9.0	8.5	42.0	17.0	0.58	0.628	25	
	M10	602R10	Red	7.0	9.0	10.5	46.0	17.0	0.62	0.668	25	
	M12	602R12	Red	7.0	9.0	13.0	49.0	17.0	0.64	0.688	25	
16	M5	603R5	Blue	8.5	10.5	5.5	39.5	21.0	0.84	0.907	25	
	M6	603R6	Blue	8.5	10.5	6.5	41.3	21.0	0.86	0.927	25	
	M8	603R8	Blue	8.5	10.5	8.5	45.5	21.0	0.93	0.997	25	
	M10	603R10	Blue	8.5	10.5	10.5	49.5	21.0	0.99	1.057	25	
	M12	603R12	Blue	8.5	10.5	13.0	54.0	21.0	1.02	1.087	25	
25	M5	604R5	Yellow	10.0	12.0	5.5	45.0	24.0	1.22	1.312	25	
	M6	604R6	Yellow	10.0	12.0	6.5	46.5	24.0	1.20	1.292	25	
	M8	604R8	Yellow	10.0	12.0	8.5	51.0	24.0	1.31	1.402	25	
	M10	604R10	Yellow	10.0	12.0	10.5	55.0	24.0	1.57	1.662	25	
	M12	604R12	Yellow	10.0	12.0	13.0	57.0	24.0	1.39	1.482	25	
35	M14	604R14	Yellow	10.0	12.0	15.0	61.5	24.0	1.49	1.582	25	
	M6	605R6	Red	12.0	14.5	6.5	49.5	27.0	1.85	2.010	25	
	M8	605R8	Red	12.0	14.5	8.5	54.0	27.0	2.00	2.160	25	
	M10	605R10	Red	12.0	14.5	10.5	59.0	27.0	2.13	2.290	25	
	M12	605R12	Red	12.0	14.5	13.0	61.0	27.0	2.12	2.280	25	
50	M14	605R14	Red	12.0	14.5	15.0	64.5	27.0	2.18	2.340	25	
	M16	605R16	Red	12.0	14.5	17.0	68.0	27.0	2.24	2.400	25	
	M6	606R6	Blue	14.0	16.5	6.5	59.0	32.0	3.00	3.220	25	
	M8	606R8	Blue	14.0	16.5	8.5	59.0	32.0	2.93	3.150	25	
	M10	606R10	Blue	14.0	16.5	10.5	63.0	32.0	3.08	3.300	25	
	M12	606R12	Blue	14.0	16.5	13.0	68.0	32.0	3.23	3.450	25	
	M14	606R14	Blue	14.0	16.5	15.0	71.5	32.0	3.32	3.540	25	
	M16	606R16	Blue	14.0	16.5	17.0	77.0	32.0	3.38	3.600	25	
	M20	606R20	Blue	14.0	16.5	21.0	83.5	32.0	3.46	3.680	25	