


Cable connections, insulated and non insulated

Insulated receptacles, bronze - tin plated



- ▶ For fine and superfine stranded conductors
- ▶ High quality bronze material provides optimum spring characteristic and improved contact strength



Characteristics

- Total cross-section: 0.5 - 6 mm²
- Acc. to DIN 46245, part 3
- Cross-section-dependent colour-coding
- Heat resistant to 70° C

Material

- CuSnZn (bronze)
- Insulation sleeve: PVC

Surface

- Tin-plated

Nominal cross section mm ²	Nominal size to DIN	Part No.	Colour	Tab thickn.	Tab width	Dimension mm			Insulation material	Weight/ 100 pcs. ~ kg	Packing unit/ pcs
						l1	l2	s			
0,5-1	6,3 - 1	720BZ	Red	0,8	6,3	22	7,5	0,45	PVC	0,09	100
1,5-2,5	6,3 - 2,5	730BZ	Blue	0,8	6,3	21	7,4	0,45	PVC	0,09	100
4-6	6,3 - 6	750BZ	Yellow	0,8	6,3	21	7,5	0,45	PVC	0,10	100

▶ Tools: see chart page 193

Insulated receptacles, multiple type



- ▶ For fine and superfine stranded conductors

Characteristics


- Total cross-section: 0.5 - 6 mm²
- Cross-section-dependent colour-coding
- Heat resistant: PVC to 70° C

Material

- CuZn (brass)
- Insulation sleeve: PVC

Surface

- Tin-plated



Nominal cross section mm ²	Part No.	Colour	Tab thickn.	Tab width	Dimension mm				Insulation material	Weight/ 100 pcs. ~ kg	Packing unit/ pcs
					l1	l2	l3	s			
0.5-1	720AZ	Red	0.8	6.3	22	7.5	8	0.4	PVC	0.11	100
1.5-2.5	730AZ	Blue	0.8	6.3	22	7.5	8	0.4	PVC	0.11	100
4-6	750AZ	Yellow	0.8	6.3	25	8.0	8	0.4	PVC	0.18	100

▶ Tools: see chart page 193